

Performance Data Sheet

Model: 3MRO401

Reverse Osmosis / Activated Carbon Drinking Water Filtration System

Use Replacement Filter(s):

3MROP411 (sediment filter), 3MROP412 (granulated carbon filter), 3MROM413 (membrane module) and 3MROP416 (carbon block post-filter)

The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system as specified in NSF/ANSI Standard 42, 53, and 58.



System tested and certified by NSF International against NSF/ANSI Standard 42, 53, and 58 for the reduction of substances as listed below.

Nominal production rate of membrane when running to atmosphere (i.e., with empty tank) at 77° F and 50 PSI is 18.95 gpd (71.73 lpd). Production varies based on pressure (fullness) of storage tank.

Contaminant Reduction Determined by NSF testing.

Contaminant Reduction	Average Influent	NSF Specified Challenge Concentration	Avg % Reduction	Average Product Water Concentration	Max Permissible Product Water Concentration	NSF Reduction Requirements	NSF Test Report
Arsenic (pentavalent)	0.50 mg/L	0.30 mg/L ± 10%	99.4%	0.002 mg/L	0.010 mg/L	N/A	J-00120929
Barium	9.4 mg/L	10 mg/L ± 10%	98.8%	0.115 mg/L	2.00 mg/L	N/A	J-00120930
Cadmium	0.029 mg/L	0.03 mg/L ± 10%	98.0%	0.0005 mg/L	0.005 mg/L	N/A	J-00121468
Chromium (Hex.)	0.31 mg/L	0.3 mg/L ± 10% (added as hexavalent)	98.5%	0.005 mg/l	0.1 mg/L	N/A	J-00120929
Chromium (Tri.)	0.30 mg/L	0.3 mg/L ± 10% (added as trivalent)	99.5%	0.002 mg/l	0.1 mg/L	N/A	J-00120930
Copper	2.7 mg/L	3.0 mg/L + 10%	98.9%	0.03 mg/L	1.3 mg/L	N/A	J-00121469
Cyst	100000 cysts/L	Minimum 50,000 cysts/L	99.98%	7 cyst/L	N/A	≥99.95%	J-00121472
Fluoride	8.8 mg/L	8.0 mg/L ± 10%	97.4%	0.23 mg/L	1.5 mg/L	N/A	J-00121467
Lead	0.16 mg/L	0.15 mg/L + 10%	98.7%	0.002 mg/L	0.010 mg/L	N/A	J-00121468
Radium 226/228	25 pCi/L	25 pCi/L ± 10%	80.0%	5 pCi/L	5 pCi/L	N/A	J-00120930
Selenium	0.09 mg/L	0.10 mg/L ± 10% (added as ½ selenite and ½ selenate)	97.9%	0.002 mg/L	0.05 mg/L	N/A	J-00121467
Total Dissolved Solids (TDS)	771	750 mg/L ± 40 mg/L (added as sodium chloride)	93.8%	48 mg/L	N/A	≥ 75%	J-00109636
Turbidity	11 NTU	11 ± 1 NTU	99.1%	<0.1 NTU	0.5 NTU	N/A	J-00121471
Chlorine Taste and Odor	2.0 mg/L	2.0 mg/L ± 10%	97.5%	0.05 mg/L	N/A	≥ 50%	J-00075601
Nominal Particulate Class I, ≥0.5 to < 1.0 µm	11,000,000 pts/mL	At least 10,000 particles/mL	92.4%	836,667 pts/mL	N/A	≥85%	J-00128445
Carbofuran	0.08 mg/L	0.08 mg/L ± 10%	89.7%	0.008 mg/L	0.04 mg/L	N/A	J-00075602
Toxaphene	0.015 mg/L	0.015 mg/L ± 10%	93.5%	0.001 mg/L	0.003 mg/L	N/A	J-00075606
P-Dichlorobenzene	0.236 mg/L	0.225 mg/L ± 10%	99.8%	0.028 mg/L	0.075 mg/L	N/A	J-00075610
O-Dichlorobenzene	1.8 mg/L	1.8 mg/L ±10%	99.5%	0.009 mg/L	0.6 mg/L	N/A	J-00075610

Performance Data Sheet

Model: 3MRO401

Reverse Osmosis / Activated Carbon Drinking Water Filtration System

Use Replacement Filter(s):

3MROP411 (sediment filter), 3MROP412 (granulated carbon filter), 3MROM413 (membrane module) and 3MROP416 (carbon block post-filter)

Application Guidelines/Water Supply Parameters			
Membrane Type	TFCM	Water Supply Parameters	
Water Supply, chlorinated or non-chlorinated		Component	Limit
		Hardness	<350 mg/L
Water Pressure	40-100 psi (276 -689 kPA)	Iron	<0.1 mg/L
Water Temperature	40° F - 100° F (4.4° C – 37.8° C)	Manganese	<0.05 mg/L
pH Range	4.0 – 11.0	Hydrogen Sulfide	0
Maximum TDS level	2000	Turbidity	<1 NTU

System Production: Nominal production rate of membrane when running to atmosphere (i.e., with empty tank) at 77° F and 50 PSI is 18.95 gpd (71.73 lpd). Production varies based on pressure (fullness) of storage tank.
 Post Filter Chlorine Taste and Odor capacity: 1,500 gallons (5,678 liters)
 System Efficiency: 13.06% Efficiency rating means the percentage of the influent water to the system that is available to the user as reverse osmosis treated water under operating conditions that approximate typical daily usage.

It is essential that the manufacturer's recommended installation, maintenance and filter replacement requirements be carried out for the product to perform as advertised. See Installation Manual for Warranty information.

Note: While the testing was performed under standard laboratory conditions, actual performance may vary.

Important Quality Assurance Requirements: These Reverse Osmosis Drinking Water Appliances contain treatment components that are critical for effective reduction of Total Dissolved Solids as well as inorganic contaminants. We strongly recommend that the user test the water a minimum of every 6 months to verify that the appliance is performing satisfactorily.

Replacement Filters:

- 3MROP411 (sediment filter)
- 3MROP412 (granulated carbon filter),
- 3MROM413 (membrane module)
- 3MROP416 (carbon block post-filter)

For estimated costs of replacement elements please call 855-3M-WATER or visit our website at www.3MWater.com



WARNING

To reduce the risk associated with the ingestion of contaminants:

- Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before and after the system. Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts.

EPA Establishment Number 070595-CT-001

NOTICE

To reduce the risk associated with property damage due to water leakage or flooding:

- Read and follow Use Instructions before installation and use of this system.

To reduce the risk of water leakage of flooding, and to ensure optimal filter performance:

- Change the disposable filter cartridge every 12 months or sooner if you observe a noticeable reduction in water flow rate.
- Change the disposable filter membrane every 36 months or sooner if you observe a noticeable reduction in water flow rate.
- Failure to replace the disposable filter cartridges & membrane at recommended intervals may lead to reduced filter performance and cracks in the filter housing, causing water leakage or flooding.
- For questions or concerns, please contact Customer Service at 1-855-3M-WATER.

Performance Data Sheet

Model: 3MRO401

Reverse Osmosis / Activated Carbon Drinking Water Filtration System

Use Replacement Filter(s):

3MROP411 (sediment filter), 3MROP412 (granulated carbon filter), 3MROM413 (membrane module) and 3MROP416 (carbon block post-filter)

Systems must be installed and operated in accordance with manufacturer's recommended procedures and guidelines. Failure to follow installation, operation, and maintenance instructions may result in leakage and will void warranty. See Installation Manual for Warranty information.

This system has been tested for the treatment of water containing pentavalent arsenic (also known as As (V), As (+5), or arsenate) at concentrations of 0.30 mg/L or less. This system reduces pentavalent arsenic, but may not reduce other forms of arsenic. This system is to be used on water supplies containing a detectable free chlorine residual or on water supplies that have been demonstrated to contain only pentavalent arsenic. Treatment with chloramine (combined chlorine) is not sufficient for complete conversion of trivalent arsenic to pentavalent arsenic. Please see the Arsenic Facts Section of the Performance Data Sheet below for further information.

ARSENIC FACT SECTION

Arsenic (abbreviated As) is found naturally in some well water. Arsenic in water has no color, taste or odor. It must be measured by a lab test. Public water utilities must have their water tested for arsenic. You can get the results from your water utility. If you have your own well, you can have the water tested. The local health department or the state environmental health agency can provide a list of certified labs. Information about arsenic in water can be found on the internet at the US Environmental Protection Agency website: www.epa.gov/safewater/arsenic.html

There are two forms of arsenic: pentavalent arsenic (also called As(V) or As+5), and arsenate) and trivalent arsenic (also called As(III), As(+3), and arsenite). In well water, arsenic may be pentavalent, trivalent, or a combination of both. Special sampling procedures are needed for a lab to determine what type and how much of each type of arsenic is in the water. Check with the labs in your area to see if they can provide this type of service.

Reverse osmosis (RO) water treatment systems do not remove trivalent arsenic from water very well. RO systems are very effective at reducing pentavalent arsenic. A free chlorine residual will rapidly convert trivalent arsenic to pentavalent arsenic. Other water treatment chemicals such as ozone and potassium permanganate will also change trivalent arsenic to pentavalent arsenic. A combined chlorine residual (also called chloramines) may not convert all the trivalent arsenic. If you get your water from a public water utility, contact the utility to find out if free chlorine or combined chlorine is used in the water system.

The 3MRO401 system is designed to reduce pentavalent arsenic. It will not convert trivalent arsenic to pentavalent arsenic. The system was tested in a lab. Under those conditions, the system reduced 0.30 mg/L (ppm) pentavalent arsenic to 0.010 mg/L (ppm) (the USEPA standard for drinking water) or less. The performance of the system may be different at your installation. Have the treated water tested for arsenic every 6 months to check if the system is working properly.

The pentavalent arsenic reduction component of this system membrane module must be replaced at the end of its useful life of 36 months. The replacement component 3MROM413 can be purchased from the original point of purchase or from 3M at www.3MWater.com / 855-3M-WATER (855-369-2837).

Performance Data Sheet

Model: 3MRO401

Reverse Osmosis / Activated Carbon Drinking Water Filtration System

Use Replacement Filter(s):

3MROP411 (sediment filter), 3MROP412 (granulated carbon filter), 3MROM413 (membrane module) and 3MROP416 (carbon block post-filter)

3M is a trademark of 3M Company.
NSF is a trademark of NSF International.
© 2014 3M Company. All rights reserved.
34-8714-4681-0

Parts and service available from:



3M Purification Inc.
400 Research Parkway
Meriden, CT 06450
www.3MWater.com
855-3M-WATER (855-369-2837)