

Multi-Test Series™

Original Equipment Replacement Cartridge



Multi-Test Filters are extended surface high efficiency air filters designed to fit the basket framework of the Farr HP® without modification. Multi-Test Filters are collapsible replacement cartridges, and are available in four nominal efficiency ranges: 20-30%, 45-55%, 80-90%.

| Size | Capacity (CFM) | | | | Effective Media Area Sq. Ft. | Initial Resistance (inches W.G.) | | | | Recommended Final P.D. (inches W.G.) |
|----------|----------------|----------|----------|----------|------------------------------|----------------------------------|----------|----------|----------|--------------------------------------|
| | MT 20/50 | MT 50/60 | MT 80/90 | MT 90/95 | | MT 20/50 | MT 50/60 | MT 80/90 | MT 90/95 | |
| 12x24x48 | 865 | 865 | 350 | 350 | 14.50 | 0.12 | 0.23 | 0.25 | 0.40 | 1.0 |
| 16x20x8 | 935 | 935 | 360 | 360 | 15.8 | 0.12 | 0.23 | 0.25 | 0.40 | 1.0 |
| 20x20x8 | 1200 | 1200 | 450 | 450 | 19.7 | 0.12 | 0.23 | 0.25 | 0.40 | 1.0 |
| 12x24x12 | 1050 | 1050 | 500 | 500 | 20.8 | 0.12 | 0.23 | 0.25 | 0.40 | 1.0 |
| 20x25x8 | 1525 | 1525 | 580 | 580 | 25.6 | 0.12 | 0.23 | 0.25 | 0.40 | 1.0 |
| 24x24x8 | 1725 | 1725 | 700 | 700 | 29.0 | 0.12 | 0.23 | 0.25 | 0.40 | 1.0 |
| 24x24x12 | 2000 | 2000 | 2000 | 2000 | 41.7 | 0.12 | 0.23 | 0.25 | 0.40 | 1.0 |
| 12x24x24 | 1500 | 1500 | 2000 | 2000 | 48.5 | 0.20 | 0.23 | 0.40 | 0.55 | 1.0 |
| 24x24x24 | 3000 | 3000 | 2000 | 2000 | 96.1 | 0.20 | 0.23 | 0.40 | 0.55 | 1.0 |



Regional Sales Offices/Distribution Centers

Atlanta, GA • Detroit, MI • East Greenville, PA* • Houston, TX*
Indianapolis, IN • Kansas City, MO • Louisville, KY* • Madbury, NH
Miami, FL • Nashville, TN • Mira Loma, CA* • Tacoma, WA

*Denotes manufacturing site.

