

Series K-40

Extended Surface Pleated Air Filters



Features

- Designed for value and economy
- Ideal for filter service programs and preventative maintenance plans
- Moisture resistant beverage-board frame
- Sturdy double-wall design
- Completely disposable

Series K-40 Filters are engineered to provide an excellent combination of rugged construction, high quality performance, and low initial cost.

The filter is a medium efficiency, extended surface pleated panel designed for use in all types of residential, commercial, and industrial air filtration systems. The value-oriented design of the Series K-40 makes it the air filter of choice in applications where filters are changed according to predetermined maintenance schedules, instead of pressure gauge readings. Series K-40 filters are offered in a wide range of popular sizes, and in thickness of 2" and 4".

The K-40 carries a MERV 8 and MERV-A 8 performance rating in accordance with ASHRAE Test Standard 52.2-2007. In addition to the Series K-40, Koch Filter manufactures a complete line of pleated panels and other air filtration products. Please consult your Koch representative for specific recommendations on the right filters for your system.

Series K-40 Technical Data

Size (Nominal)	Size (Actual)	Capacity CFM	Resistance At 500 CFM	Media Area (SQ. FT.)
12x24x2	11-3/8 x 23-3/8 x 1-3/4	1000	0.24	4.9
16x20x2	15-1/2 x 19-1/2 x 1-3/4	1100	0.24	5.8
16x25x2	15-1/2 x 24-1/2 x 1-3/4	1390	0.24	7.0
20x20x2	19-1/2 x 19-1/2 x 1-3/4	1390	0.24	7.0
20x25x2	19-1/2 x 24-1/2 x 1-3/4	1740	0.24	8.8
24x24x2	23-3/8 x 23-3/8 x 1-3/4	2000	0.21	10.1
12x24x4	11-3/8 x 23-3/8 x 3-5/8	1000	0.21	8.0
24x24x4	23-3/8 x 23-3/8 x 3-5/8	2000	0.21	16.0



Regional Sales Offices/Distribution Centers

Atlanta, GA • Detroit, MI • East Greenville, PA* • Houston, TX*
Indianapolis, IN • Kansas City, MO • Louisville, KY* • Madbury, NH
Miami, FL • Nashville, TN • Mira Loma, CA* • Tacoma, WA

*Denotes manufacturing site.



KOCH FILTER[®]

8401 Air Commerce Drive, Louisville, KY 40219
Phone: 502.634.4796 | Fax: 502.637.2280
info@kochfilter.com | www.kochfilter.com