



PRODUCT BULLETIN

SUBJECT **SPRAYSTOP STK** High Efficiency Synthetic Paint Arrestor Bulletin No. PB-798-9

SprayStop STK is an extremely durable paint arrestor composed of 100% multi-denier synthetic fibers. These fibers are arranged in a progressively dense configuration, coarse on the air entering and becoming finer toward the air exiting side of the media. This graduated density allows paint particles to permeate the pad from the back to front. This full depth loading enables **SprayStop STK** to provide up to 96% removal efficiency when used to collect aerospace primers and powder coat materials. With longer service life and less down time; the unique capabilities of **SprayStop STK** protect against stack contamination and provide maximum achievable control of chromate-laden primers and other coating materials.

The upstream side of **SprayStop STK** is red in color, while the downstream is tinted purple to ensure correct installation. The binders used in **SprayStop STK** are acrylic; no harmful halogens are utilized.

SprayStop STK is an excellent paint arrestor for all types of air-dry coating materials. The media effectively removes overspray solids from lacquers and air dry enamels. STK media is a durable media that can be vacuumed and re-used, making it an ideal choice as a primary filter for cost-effective source capture.

SprayStop STK is available in 3/8" thick pre-cut pads or blankets, service rolls, and economical bulk rolls.

PRODUCT PERFORMANCE DATA	
TEST AIR FLOW	200 fpm
INITIAL PRESSURE DROP	0.14" wg
RECOMMENDED FINAL RESISTANCE	1.0" wg
FRACTIONAL EFFICIENCY @ 5+ MICRONS	96% AVERAGE
@ 3 MICRONS	79.5% AVERAGE
FILTER CONSTRUCTION	100% DUAL DENSITY MEDIA



Koch Filter Corporation
Filtration Products Crafted with Pride